

N 930. Führungssäule mit Bund Easy-Mount-Line nach DIN 9825, ISO 9182-5

Bestellbeispiel:

N930.63.224 Führungssäule mit Bund,
d1 = 63 mm, L = 224 mm

d1	15/16	19/20	24/25	30/32	38/40	48/50	63	80
d2	22	25	32	40	50	63	80	95
d3	22	25	32	40	50	60	70	93
d4	33	36	43	51	61	74	91	106
d7	45,7	48,7	55,7	63,7	73,7	86,7	103,7	118,7
M	M6	M6	M6	M8	M8	M8	M8	M8
b	15,5	17,4	19,3	21,9	24,3	27,8	32	35
b1	21,3	23,5	26,8	31,3	35,5	41,5	49	54,1
M i	M8	M8	M8	M8	M8	M8	M8	M12
L1	20	23	30	37	37	47	47	60

L	15/16	19/20	24/25	30/32	38/40	48/50	63	80
100	●	●	●	○				
112	●	●	●	●				
125	●	●	●	●	●			
140	●	●	●	●	●	●		
160	●	●	●	●	●	●	●	
180	●	●	●	●	●	●	●	
200	●	●	●	●	●	●	●	
224				●	●	●	●	●
240				●	●	●	●	○
250			●	●	●	●	●	●
260				●	●	●	●	○
280				●	●	●	●	○
315				●	●	●	●	●
355					●	●	●	●
400						●	●	●

bis $\varnothing 32$ mm = 3 Haltestücke M6
ab $\varnothing 38$ mm = 4 Haltestücke M6



Easy-Mount-Line

Produkteigenschaften

Material: Stahl, 18NiCrMo5, gehärtet 62-64 HRC

Ausführung: feingeschliffen und subfinit Easy-Mount-Line

Lieferumfang: inkl. 3 bzw. 4 Haltestücke



Zeichnung zu N 930.

